


BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M Ltd. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

REFER DRAWING:- 008032987U91

REF PART NO: 007537379C11

UNSPECIFIED TOLERANCES FOR PART		SURFACE FINISH SYMBOLS:ISO-1302		 MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA					
FORMING TO FORMING	UPTO 500 ±0.5 ABOVE 500 ±0.8	WELDING SYMBOLS:IS813							
		REMOVE ALL SHARP CORNERS & BURRS							
CD BETWEEN HOLES	IN ONE PLANE ±0.2 IN DIFF PLANES±0.5	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0		NAME	DATE	PROJECT CODE:		
FORM TO PIERCE	±0.5		<CC> COUNT↙: 0		DSNR	AR	29-05-2023	ER NUMBER:ER23C0000228	
HOLE SIZES	+0.2/-0		WEIGHT(kg) : 0.38		CHKR	NVC	29-05-2023	DESCRIPTION :	
SLOT SIZES	±0.8		S/F AREA(cm²): 128		APPR	DS	29-05-2023	BRAKE PIVOT BUSH	
FLANGE WIDTH	+1.0/-0.7		MATERIAL:					PART NUMBER :	CL:
JOGGLE DEPTH	+0.3/0		FE 410 W AS PER IS-2062					008032988U01	NA
UNSPECIFIED TOLERANCES FOR PART & ASSEMBLY					DWG.SIZE : A4		SCALE : 1:1		SHEET: 1 OF 1
GENERAL TOLERANCES	UP TO 300 ±0.8 ABOVE 300 ±1.0								
ANGULAR TOLERANCE	±1°								